

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (original) An electrical connector, comprising:
  - a housing including an inner bore and an open end providing access to said inner bore, said inner bore having an inner surface and a bore retaining groove disposed in said inner surface;
  - a piston-contact element slidably received in said inner bore of said housing through said open end, said piston-contact element being axially movable between retracted and advanced positions and having an outer surface with an element retaining groove disposed in said outer surface; and
  - a resilient member received in each of said retaining grooves releasably retaining said piston-contact element in one of said retracted and advanced positions within said inner bore of said housing.
2. (original) An electrical connector according to claim 1, wherein
  - said piston-contact element is in said retracted position when said resilient member is received in said first and second retaining grooves; and
  - said piston-contact element is in said advanced position when said resilient member is received in said bore retaining groove and spaced from said element retaining groove.
3. (original) An electrical connector according to claim 1, wherein
  - said piston-contact element includes opposing first and second ends;
  - said first end is adapted to engage another electrical connector; and
  - said second end includes a stop substantially preventing removal of contact member from said inner bore of said housing.

4. (original) An electrical connector according to claim 3, wherein  
said stop comprises an annular shoulder abutting said resilient member in the  
other of said retracted and advanced positions.
5. (original) An electrical connector according to claim 3, wherein  
said first end of said piston-contact element includes probe fingers; and  
said second end is a piston.
6. (original) An electrical connector according to claim 5, wherein  
said probe fingers and said piston-contact element together form a unitary, one-  
piece member.
7. (original) An electrical connector according to claim 1, wherein  
said retaining grooves are each substantially annular and continuous.
8. (original) An electrical connector according to claim 1, wherein  
said bore retaining groove includes first and second side walls and an end wall  
extending therebetween; and  
an angled wall extends from said second side wall facilitating engagement of said  
resilient member in said first groove.
9. (original) An electrical connector according to claim 1, wherein  
said element retaining groove includes first and second side walls and an end wall  
extending therebetween, said second side wall being angled with respect to  
said first side wall facilitating disengagement of said resilient member from  
said second groove.
10. (original) An electrical connector according to claim 1, wherein  
said resilient member is a substantially ring shaped spring.

11. (original) An electrical connector according to claim 10, wherein  
said resilient member includes a slot allowing expansion and compression of said  
resilient member.
12. (original) An electrical connector according to claim 1, wherein  
an electrical contact of another electrical connector is received in said inner bore  
of said housing through said open end engaging said piston-contact element.
13. (original) An electrical connector according to claim 1, wherein  
said housing includes an inner conductive sleeve; and  
said bore retaining groove is disposed in said conductive sleeve.
14. (original) An electrical connector according to claim 1, wherein  
said electrical connector is a high-voltage bushing insert.
15. (original) A method of operating first and second electrical connectors under a load  
when an arc is created during a fault, comprising the steps of:  
inserting a second contact element of the second connector in an inner bore of a  
housing of the first electrical connector toward a first piston-contact element  
thereof;  
generating gas from the arc developed between the separated contact elements;  
directing the gas to apply a force to move the first piston-contact element in a  
direction toward the second contact element;  
expanding a resilient member located in both a bore retaining groove in the inner  
bore and a element retaining groove located in the piston-contact element,  
thereby spacing the resilient member from the element retaining groove and  
permitting movement of the piston-contact element from a retracted position  
within the inner bore by the application of the force of gas; and

moving the piston-contact element to an advanced position for engaging the second contact element to provide an electrical connection between the first and second contacts to quench the arc.

16. (original) A method according to claim 15, wherein  
a tapered protrusion on the piston-contact element expands the resilient member until the resilient member is spaced from the element retaining groove.
17. (original) A method according to claim 15, wherein  
the piston-contact element moves toward the second contact element until the resilient member engages a stop member on the piston-contact element.
18. (original) A method according to claim 15, wherein  
said resilient member is a substantially ring-shaped spring.
19. (original) An electrical connector according to claim 1, wherein  
said first electrical connector is a high-voltage bushing insert.
20. (original) A method according to claim 15, wherein  
said second electrical connector is an elbow cable connector.